

INSPECTOR SIGNATURE: __

Auto Tech Sheet

(For Office Use) Member #

Name:	Run Group:	Car#
Model/Year:	Car Color:	Eng. Disp.:
Run Groups: C: Novice • B: Experience D: Competition Licen	ced • A: Fastest Cars/Most Experienced Dr	ivers • O: Open Wheel/Single Seater
Pass Fail	·	
2. APPAREL - Full-length par Highly recommended, but r similar fire-resistant materi 3. SEAT BELTS - Group C ar 6- point. All securely ancho	or later required for all (Snell SA sticker mants, long sleeved cotton shirts, cotton socks a not mandatory are drivers' suits, driving gloves als. Arm restraints required for All Open Cars and Group B. original factory installed belts Group, Metal-to-metal, with large diameter washonly on factory seats. Harness and Seats must	nd full coverage shoes are mandatory. s and shoes all made of Nomex or s. cup A; Race Seat = 5/6-Point. <u>OR</u> Stock Seat = ters on both sides of floor mounting holes.
BC or ABC rated and fully o	ecommended but not required. Securely anch charged. AFFF or Halon recommended. Group-Full roll cage required. A Group- Roll b	nored metal-to-metal in reach of driver. Doar minimumThe same Roll Protection is highly
5a. CONVERTIBLES- Conve bar. All occupants must pa 6. PEDALS - Free return and	ot required for other Classes. ertibles must have structural roll protection insides the "broom stick" test measured from the table in good operating condition. Firm brake pedatove all loose items from trunk and interior, inclined	ıl.
pockets, console, mats, etc 8. AIR BAG EQUIPPED CAR 9. WINDSHIELD - No major of	c. Glove box locked. Spare secured or removes PNO Obstructions in front of Air Bag (s). Cracks and functional wipers with good blades ide (two highly recommended) and one secure	ved .
13. FRONT SUSPENSION - N condition. Tie rods secure.	to suspension or chassis parts that affect the lo excessive looseness in steering or suspens Axle boots & oil seals in good condition.	sion. Shock bolts tight. Ball joints in good
No positive camber on any15.WHEEL BEARINGS - Coru16.BRAKES - Sufficient brake	rect adjustment, check for play & proper lubrice linings or pads. No rubbing, cuts or abrasion	cation, no damaged or burnt bearings. s in brake lines. Check rotor condition.
Make sure you start with ar with fresh Competition pade	be checked periodically for 2mm minimum thion mple brake pad material and/or bring an extra s properly bedded in. bends. All lug nuts must have 94 - 96 lbs. toro	set of pads. It is recommended you start
airtight cap. Hubcaps and (Center Caps must be removed.	•
contact patch area (race tir	No cracks or bulges. ZR or better required. No cracks or bulges. ZR or better required. No es or shaved performance tires must have as each an experienced driver with like car/tires for	least 1/16" tread wear marker depth
specification or better brake run less than 90 days prior	must show in reservoir. All cars must have the fluid 90 days or less preceding the high-spe to this event, then the fluid must be flushed a	ed event. If another high-speed event is gain before running.
Terminal on All batteries m 21. ENGINE - Check for odd s	y fastened and in good condition. No acid lea ust be covered by cap or tape. ounds and satisfactory exhaust (105db limit)	ks or corrosion. The Positive (+)
24.THROTTLE RETURN - Fre	s and leaks of any fluid - oil, gas, brake, or coo eely operating and good springs.	
IN CONSIDERATION OF MY PARTICIPATION EXCEED THE REQUIREMENTS. I AGREE To responsibility for the condition and my car or its occupants as a result of safety and roadworthiness of my car.	N AT AUTOBAHN CC, I HAVE CHECKED THE AE TO: indemnify and hold harmless Autobahr preparation of my car, or any subsequent any such failures. I acknowledge that at al I hereby certify that I have no physical or	uipped) must be functional. (O Group excluded). BOVE ITEMS AND CERTIFY THAT THEY MEET OR a Country Club, or their agents, with respect mechanical failures or resulting damage to I times, I remain solely responsible for the mental problems, which could jeopardize
	HAVE BEEN TESTED AND SERVICED AS DESC	RIBED. THE TECH INSPECTOR'S SIGNATURE THE DRIVER'S SIGNATURE, WHICH WARRANTS
DRIVER'S SIGNATURE:		DATE:

_____ DATE:___